

 <b>BAZAN GROUP</b> GADIV PETROCHEMICAL INDUSTRIES LTD	<b>Para - XYLENE SPECIFICATION</b>		
	Revision 01	Updated: December 30, 2024	Spec No. X725
Certified ISO-9001 / ISO 14001 / ISO 45001			

<u>PROPERTY</u>	<u>UNIT</u>	<u>MIN</u>	<u>MAX</u>	<u>METHOD</u>
Appearance (at 18-25 °C)	---	Clear liquid, free from sediments		
Density at 15 °C	Kg/L	0.864	0.867	ASTM D 4052
Distillation Range, 138.3°C included	°C		1.0	ASTM D 850
para-Xylene Assay	% w/w	99.60		ASTM D 7504
meta-Xylene content	% w/w		0.3	ASTM D 7504
ortho-Xylene content	% w/w		0.1	ASTM D 7504
Ethyl Benzene content	% w/w		0.15	ASTM D 7504
Non-Aromatics content	% w/w		0.05	ASTM D 7504
Toluene content	% w/w		0.1	ASTM D 7504
Bromine Index	---		20	ASTM D 2710
Total Sulphur	mg/kg		1.0	ASTM D 7183
Total Chlorine	mg/kg		1.0	ASTM D 7536
Acid wash color	---		1	ASTM D 848
Color	Pt/Co Scale		10	ASTM D 1209
H2S, SO2 content	---	Negative		ASTM D 853

**Dr. Yulia Gerchikov**



**Chief Chemist**