
 <b>BAZAN GROUP</b> GADIV PETROCHEMICAL INDUSTRIES LTD	<b>SOLGAD 150 SPECIFICATION</b>		
	Revision 14	Updated: January 13, 2025	Spec No. S703
Certified ISO-9001 / ISO 14001 / ISO 45001			

<u>PROPERTY</u>	<u>UNIT</u>	<u>MIN</u>	<u>MAX</u>	<u>METHOD</u>
Appearance (at 18-25 °C)	---	Clear liquid, free from sediments		
Density at 15 °C	Kg/L	0.88		ASTM D 4052
Density at 20 °C	Kg/L	To be reported		ASTM D 4052
Distillation: IBP	°C	180		ASTM D 86
Distillation: FBP	°C		210	ASTM D 86
Copper corrosion	No.		1	ASTM D 849
Total Aromatics content	% w/w	99.0		ASTM D 7504
Non-Aromatics content	% w/w		1.0	ASTM D 7504
Cumene content	% w/w		0.1	ASTM D 7504
Naphthalene content	% w/w	To be reported		ASTM D 7504
H <sub>2</sub> S, SO <sub>2</sub> content	---	Negative		ASTM D 853
Color	Pt/Co Scale		20	ASTM D 1209
Bromine Number	---		1	ASTM D 1159
Flash point	°C	65		ASTM D 93

**Dr. Yulia Gerchikov**



**Chief Chemist**