



BAZAN GROUP

GADIV PETROCHEMICAL
INDUSTRIES LTD

Certified ISO-9001 / ISO 14001 / ISO 45001

SOLGAD 200 ND

Revision 03

Updated March 12, 2023

Spec No. S714

PROPERTY	UNITS	MIN	MAX	METHOD
Appearance (at 18-25°C)	---	Clear liquid, free from sediments		
Color		Light yellow		Visual
Density at 15 Deg C	Kg/l	0.962	0.995	ASTM D 4052
Distillation: IBP	Deg C	225.0		ASTM D 86
Distillation: FBP	Deg C		300.0	ASTM D 86
Total Aromatics Content	% w/w	99.0		ASTM D 4492
Non Aromatics Content	% w/w		1.0	ASTM D 4492
Naphthalene Content	% w/w		0.9	ASTM D 4492(MOD)
Water Content	mg/kg		300	ASTM D 6304
Refractive Index @ 20 Deg C	---	1.507	1.607	ASTM D 1218
Copper Corrosion	No.		1	ASTM D 849
Flash Point	Deg C	100		ASTM D 93
Total Sulfur	mg/kg		10	ASTM D 5453/ D 7183

Dr. Avi Meshulam
Chief Chemist

Gadiv

Bazan Ltd